		Approved For Re	elease 2006/03/18	: CIA-RE	P82-00457R	Cosament Sa		
	FORM NO. 51-44 FEB 1952	MA	CENTRAL IN		TIAL NCE AGENCY	No Change in Glass  Declarated To: Change To: Auth.: HR 73.2  Data: 1 1 SEP 1976	TS S	0
		CLASSIFICATION		IRUL - 13	.S. OFFICIA		25X1	25X1
,			INFORM <i>A</i>	TION	REPORT		23/(1	
	•		- -			CD NO.		
	COUNTRY	Hungary				DATE DISTR.	19 N	larch 195
<b>(1</b>	SUBJECT	Electric Power an	d Errigation Pr	r <b>o</b> ject		NO. OF PAGES	1	
					<b>**</b> **********************************	NO. OF ENCLS.		
						SUPPLEMENT TO REPORT NO.		25X1
5X1	OF THE UNITED S AND 794, OF THE	ONTAINS INFORMATION AFFECTING THE TATES, WITHIN THE MEANING OF TITLI U.S. CODE, AS AMENDED. ITS TRAI UNTENTS TO OR RECEIPT BY AN UNAU	E 18, SECTIONS 793 RSMISSION OR REVE-	1	'HIS IS UNE'	VALUATED INFORMAT	ION	

PROBESTED BY LAW. THE REPRODUCTION OF THIS FORM IS PROBIBITED.

- 1. A shortage in electric power led the Hungarian government to resume the trans-Misza irrigation project, which was interrupted by World War II. The largest single plant under this project is the partially completed one at Tiszalök.
- 2. The hydro-electric plant of the Miszalök reservoir will have a capacity of 10,000 kw. It will consist of three turbines and it is hoped that, with due consideration to the average water level of the Tisza, it will be able to produce approximately 55-60 kwh (sic) of power in a year. This quantity of power would mean a saving of 10,000 carloads of coal.
- 3. The Tiszalök reservoir consists now of three locks, each with a clearance of 37 meters, and is designed to raise the water level of the Tisza to a height of 7 1/2 meters. Along the reservoir a 17-meter-wide and 85-meterlong mayigable sluide is teing built for the accommodation of 1,000-ton ships and barges. As a result the Tiska will become navigable as far as Dombrad. The reservoir will supply, at mean water level, 60 cubic meters of water per minute for the main trans-Pisza canal. This canal will cross the Alfold (the Great Plain) in a length of 97 km. of which 25 km. are completed; it will empty through the Bereityo River into the Koros River.
- 4. The Riszalök construction project is under the direction of the Russian engineer Eliava (fou). According to the plans, 6 million cubic meters of earth will be movel and 100,000 cubic meters of concrete and reinforced concrete walls will be built, requiring 25,000 carloads of cement and 320 carloads of reinforcing concrete; in addition, 120,000 cubic meters of gravel and 95,000 cubic meters of stone will be used. It is planned to employ approximately 2,500 tons of steel flooring for the foundation as protection against undersoil water.
- 5. The entire machine equipment will be manufactured in Hungary, for the most part in the various plants of the Ganz company. Work on the project was begun in February 1950 and the completion is planned for the end of 1952.

CLASSIFICATION SECRET/COMPROL > U.S. OFFICIALS ONLY

	T	X . W.	
STATE TO NAVY	NSRB	STATE TONT I BE	
		<del>                                      </del>	
1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A	FRI	11111111111111111111111111111111111111	
			<del></del>

## BEST COPY Available